



9-Technical Characteristics

VIEILLITHEQUE

-Ageing cabinets- I temperature

Model n°	Dimensions (mm)			Weight kg (empty)	Elec. Pwr.	Max. Current	Voltage AC (V)	Voltage Tolerance	Frequenc y (Hz)
	H	W	D						
JC-103 (50 bottle)	840	595	600	53	92W	0.6A	110- 120V	+10 /-10	50
JC-188 (100 bottle)	1240	595	600	68	92W	0.6A	110- 120V	+10 /-10	50
JC270 (150 bottle)	1640	595	600	83	122 W	0.8A	110- 120V	+10 /-10	50

SERVITHEQUE

-Ageing Cabinets- I temperature

Model n°	Net Dimensions " (mm)			Weight lb. (kg) (empty)	Elec Pwr.	Max. Curre nt	Voltage AC (V)	Voltage Tolerance	Freque ncy (Hz)
	H	W	D						
JC-103 (50 bottle)	33.07" (840)	23.4" (595)	23.6" (600)	116.74 (53)	113 W	0.8A	110- 120V	+10 /-10	50
JC-188 (100 bottle)	48.81" (1240)	23.4" (595)	23.6" (600)	149.78 (68)	137 W	0.87A	110- 120V	+10 /-10	50
JC270 (150 bottle)	64.57" (1640)	23.4" (595)	23.6" (600)	182.82 (83)	175 W	1.1A	110- 120V	+10 /-10	50

9-Technical Characteristics (continue)

	Gas	Operating Limits		Consumption over 24h	Regulation Precision	Display Precision
		Min. T.	Max. T.			
JC-103 (50 bottle)	R134a	32°F (0°C)	92°F (35°C)	0.6 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)
JC-188 (100 bottle)	R134a	32°F (0°C)	92°F (35°C)	0.6 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)
JC270 (150 bottle)	R134a	32°F (0°C)	92°F (35°C)	0.8 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)

	Gas	Operating Limits		Consumption over 24h	Regulation Precision	Display Precision
		Min. T.	Max. T.			
JC-103 (50 bottle)	R134a	54°F (12°C)	92°F (35°C)	0.6 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)
JC-188 (100 bottle)	R134a	54°F (12°C)	92°F (35°C)	0.7 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)
JC270 (150 bottle)	R134a	54°F (12°C)	92°F (35°C)	0.8 kwh	+/- 4.3°F (+/- 2.5°C)	+/- 1.7°F (+/- 1°C)